



Gender Classification based on Facial information



**IMTNAN QAZI
ALINA OPREA
KATERINE DIAZ
INAYATULLAH KHAN**

*16TH SUMMER SCHOOL ON IMAGE PROCESSING
JULY 7TH-16TH 2008, VIENNA, AUSTRIA.*

JULY 15, 2008.


The project team



2



Layout



3

- **Problem statement.**
- **State of the Art.**
- **The system overview.**
 - Principal Component Analysis.
 - Fisher Linear Discriminator.
 - Common Vector method.
 - Support Vector Machines.
- **Simulations & Results.**
- **Conclusion.**
- **Future Perspectives.**

Gender classifier based on Facial information

Problem statement.

State of the Art.

Principal Component
Analysis.

Fisher Linear
Discriminator.

Common Vector method.



Support Vector
Machines.

Simulations & Results.

Conclusion.

Future Perspectives.

- **Men and Women: Same Species, Different Planets**



- **Mathematical/Image processing
viewpoint:**

- Binary classification:

- ✦ provided limited prior information.
- ✦ An elevated difficulty level for local probability distribution modeling of the test data.

Gender classifier based on Facial information

Problem statement.

State of the Art.

Principal Component Analysis.

Fisher Linear Discriminator.

Common Vector method.

Support Vector Machines.


Simulations & Results.

Conclusion.

Future Perspectives.

Local features

- Skin colour, shape & size of the face, amount of hairs, shape & colour of the lips...
- Higher difficulty level.
- Classification accuracies are mediocre.



Global features

- Whole facial signature considered as a complete feature set.
- Useful training sequences required.
- Higher classification accuracies.
- Subspace methods + Statistical Learners:
 - ✦ Principal Component Analysis (*PCA*).
 - ✦ Fisher Linear Discriminator (*FLD*).
 - ✦ Common Vectors (*CV*).
 - ✦ Support Vector Machines (*SVM*).

.....

Gender classifier based on Facial information

Problem statement.

State of the Art.

The system overview.

Principal Component Analysis.

Fisher Linear Discriminator.


Common Vector method.

Support Vector Machines.

Simulations & Results.

Conclusion.

Future Perspectives.



Gender classifier based on Facial information

Problem statement.

State of the Art.

System overview.

Principal Component Analysis.

Fisher Linear Discriminator.


Common Vector method.

Support Vector Machines.

Simulations & Results.

Conclusion.

Future Perspectives.

- Karhunen-Loeve Transform (*KLT*). 
- Maps vectors from an M - d space to a n - d space ; $n \ll M$.
- Computes eigenvectors of the *covariance* matrices for normal distributions.

$$C = \frac{1}{r} \sum_{j=1}^r d_j d_j^T, \quad Z = (z_1, z_2, \dots, z_n)^T$$

$$\varepsilon_i = \|Z_{\text{new}} - Z_i\|$$

$$s = \arg \min_i [\varepsilon_i]$$

- Other distances can also be used.
- *Optimal linear dimensionality reducer.*

Gender classifier based on Facial information

Problem statement.

State of the Art.

System overview.

Principal Component Analysis.

Fisher Linear Discriminator.

Common Vector method.


Support Vector Machines.

Simulations & Results.

Conclusion.

Future Perspectives.

- Supervised method.
- Label information considered.
- Inter-class & Intra class *scatter matrices*; proportional to covariance matrices.



$$J(\mathbf{w}) = \frac{\mathbf{w}^T S_B \mathbf{w}}{\mathbf{w}^T S_W \mathbf{w}}, \quad S_B = \sum_c N_c (\mu_c - \bar{\mathbf{x}})(\mu_c - \bar{\mathbf{x}})^T$$

$$S_W = \sum_c \sum_{i \in c} (\mathbf{x}_i - \mu_c)(\mathbf{x}_i - \mu_c)^T$$

$$S_W^{-1} S_B \mathbf{w} = \lambda \mathbf{w}$$

- Generalized eigenvalue problem.
- Choice of suitable eigenvalue & eigenvector for the solution.
- Largest eigenvalue is chosen.

Gender classifier based on Facial information

Problem statement.

State of the Art.

System overview.

Principal Component Analysis.

Fisher Linear Discriminator.

Common Vector method.

Support Vector Machines.

Simulations & Results.

Conclusion.

Future Perspectives.

- Feature space is divided in two orthogonal subspaces.
- Each sample in training sequence:

$$x_m^i = x_{m,\text{dif}}^i + x_{\text{com}}^i + \varepsilon_m^i, \quad i = 1, \dots, C; m = 1, \dots, N_i$$

- Difference subspace is equal to the rank of scatter matrix for each class.


$$x_{\text{com}}^i = x_m^i - P_{RS}^{(i)} x_m^i$$

- Minimizes the criterion:

$$\min \left(\sum_{m=1}^{N_i} \|x_m^i - x_{m,\text{dif}}^i - x_{\text{com}}^i\|^2 \right)$$

which takes the form:

$$g(x_{\text{test}}) = \arg \min_{i=1, \dots, C} (\|x_{\text{test}}^i - x_{\text{com}}^i\|)$$



Gender classifier based on Facial information

Problem statement.

State of the Art.

System overview.

Principal Component
Analysis.

Fisher Linear
Discriminator.

Common Vector method.


Support Vector Machines.

Simulations & Results.

Conclusion.

Future Perspectives.

- Optimal separating hyper plane.
- Function that predicts best response from some training functions.
- Given, observation-label pairs:



$$(\mathbf{x}_i, y_i), i = 1, \dots, l$$

- Minimizes the criterion:

$$\min_{\mathbf{w}, b, \xi} \quad \frac{1}{2} \mathbf{w}^T \mathbf{w} + C \sum_{i=1}^l \xi_i$$

$$y_i(\mathbf{w}^T \phi(\mathbf{x}_i) + b) \geq 1 - \xi_i \quad , \quad \xi_i \geq 0$$

- Kernel function:

$$K(\mathbf{x}_i, \mathbf{x}_j) \equiv \phi(\mathbf{x}_i)^T \phi(\mathbf{x}_j)$$

Gender classifier based on Facial information

Problem statement.

State of the Art.

System overview.

Principal Component Analysis.

Fisher Linear Discriminator.



Common Vector method.

Support Vector Machines.

Simulations & Results.

Conclusion.

Future Perspectives.



Stability analysis of PCA

Gender classifier based on Facial information

Problem statement.

State of the Art.

System overview.

Principal Component Analysis.

Fisher Linear Discriminator.



Common Vector method.

Support Vector Machines.

Simulations & Results.

Conclusion.

Future Perspectives.



Stability analysis of FLD

Gender classifier based on Facial information

Problem statement.

State of the Art.

System overview.

Principal Component Analysis.

Fisher Linear Discriminator.



Common Vector method.

Support Vector Machines.

Simulations & Results.

Conclusion.

Future Perspectives.



Stability analysis of CV

Gender classifier based on Facial information

Problem statement.

State of the Art.

System overview.

Principal Component Analysis.

Fisher Linear Discriminator.


Common Vector method.

Support Vector Machines.

Simulations & Results.

Conclusion.

Future Perspectives.



Stability analysis of SVM

Gender classifier based on Facial information

Problem statement.

State of the Art.

System overview.

Principal Component Analysis.

Fisher Linear Discriminator.



Common Vector method.

Support Vector Machines.

Simulations & Results.

Conclusion.

Future Perspectives.



Stability analysis of PCA + SVM

Gender classifier based on Facial information

Problem statement.

State of the Art.

System overview.

Principal Component
Analysis.

Fisher Linear
Discriminator.

Common Vector method.

Support Vector Machines.

Simulations & Results.

Conclusion.

Future Perspectives.

Accuracy (%age)			
Classifier	Male	Female	Overall
PCA	70	90	80
FLD	100	90	95
CV	70	100	85
SVM	90	80	85
PCA+SVM	60	100	80

Gender classifier based on Facial information

Problem statement.

State of the Art.

System overview.

Principal Component Analysis.

Fisher Linear Discriminator.

Common Vector method.

Support Vector Machines.

Simulations & Results.

Conclusion.

Future Perspectives.



Gender classifier based on Facial information

Problem statement.

State of the Art.

System overview.

Principal Component Analysis.

Fisher Linear Discriminator.

Common Vector method.

Support Vector Machines.

Simulations & Results.

Conclusion.

Future Perspectives.



Gender classifier based on Facial information

Problem statement.

State of the Art.

System overview.

Principal Component Analysis.

Fisher Linear Discriminator.

Common Vector method.


Support Vector Machines.

Simulations & Results.

Conclusion.

Future Perspectives.

- Thank GOD!! My mind can recognize female faces easily. 😊
- Stability of different methods depends on number of training sequences.
- PCA & SVM prove to be stable and reliable global classifiers with acceptable accuracy.
- Using PCA as dimension reducer and SVM as a classifier can produce better results, if more training sequences can be used.



Gender classifier based on Facial information

Problem statement.

State of the Art.

System overview.

Principal Component Analysis.

Fisher Linear Discriminator.

Common Vector method.


Support Vector Machines.

Simulations & Results.

Conclusion.

Future Perspectives.

- Tests with larger databases.
- In depth stability analysis of different global classifiers.
- Other techniques like Neural Networks may be used to validate different conclusions drawn.
- To find a funding source to attend the next summer school. 😊



Thank You!!